The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information							39-42-21 =	086-45-43 = -
Indiana [18] Putnam County [133]		Unknown [00000] 0.4 km N of CR 300N			39.705833	86.761944		
6700057 Highway agency district 1		Owner County Highway	wner County Highway Agency [02] Maintenance responsibility			County Highway A	Agency [02]	
Route 75 ROAD 500 EAST		Toll On fre	Toll On free road [3] Features intersected CLEAR Cr					
Design - Main Steel [3] Truss - Thrush	ı [10]	Design - approach 0 Other	[00]	Kilometerpoint 0 km Year built 1915 Skew angle 0 Historical significance	Structure F		m! e for the NRHP. [3]	
Total length 27.4 m = Inventory Route, Total		ngth of maximum spa e 4.7 m = 15.4 ft	an 26.8 m = 87.9 ft Curb or sidewalk wi	Deck width, out-to-out $0 \text{ m} = 0.0 \text{ f}$			dway width, curb-to-c	0 m = 0.0 ft
Deck structure type Type of wearing surface Deck protection		Nood or Timber [8] Nood or Timber [7]						
Type of membrane/we	aring surface							
Weight Limits								
Bypass, detour length 0.2 km = 0.1 mi	Bypass, detour length 0.2 km = 0.1 mi Method to determine inventory rating Method to determine operating rating		No rating analysis pe		entory rating erating rating	4.5 metric ton = 5.4 metric ton =		
	Bridge posting	20.0 - 29.9 % below	w [2]	Des	sign Load			

Functional Details	
Average Daily Traffic 100 Average daily tr	uck traffi 3 % Year 2007 Future average daily traffic 150 Year 2027
Road classification Local (Rural) [09]	Lanes on structure 1 Approach roadway width 3.9 m = 12.8 ft
Type of service on bridge Highway [1]	Direction of traffic One lane bridge for 2 - way traffic [3] Bridge median
Parallel structure designation No parallel structure	e exists. [N]
Type of service under bridge Waterway [5]	Lanes under structure 0 Navigation control
Navigation vertical clearanc 0 = N/A	Navigation horizontal clearance 0 = N/A
Minimum navigation vertical clearance, vertical lift brid	dge 0 m = 0.0 ft Minimum vertical clearance over bridge roadway 4.41 m = 14.5 ft
Minimum lateral underclearance reference feature Fe	eature not a highway or railroad [N]
Minimum lateral underclearance on right 0 = N/A	Minimum lateral underclearance on left 0 = N/A
Minimum Vertical Underclearance 0 = N/A	Minimum vertical underclearance reference feature Feature not a highway or railroad [N]
Appraisal ratings - underclearances N/A [N]	
Danain and Dankasansant Dlana	
Repair and Replacement Plans	
Type of work to be performed	Work done by Work to be done by contract [1]
Replacement of bridge or other structure because of substandard load carrying capacity or substantial	Bridge improvement cost 550000 Roadway improvement cost 550000
bridge roadway geometry. [31]	Length of structure improvement 38.1 m = 125.0 ft Total project cost 1100000
	Year of improvement cost estimate 2007
	Border bridge - state Border bridge - percent responsibility of other state
	Border bridge - structure number

Inspection and Sufficiency									
Structure status Posted for lo	ad [P]	Appraisal ratings - structural	Basically intolerable requiring high priority of replacement [2]						
Condition ratings - superstructur Serious [3]		Appraisal ratings - roadway alignment	Somewhat better than minimum adequacy to tolerate being left in place as is [5]						
Condition ratings - substructure	Poor [4]	Appraisal ratings - deck geometry	Equal to present minimum criteria [6]						
Condition ratings - deck	Fair [5]								
Scour	Bridge foundations determine	Bridge foundations determined to be stable for assessed or calculated scour condition. [5]							
Channel and channel protection	Bank is beginning to slump. If minor stream bed movement	Bank is beginning to slump. River control devices and embankment protection have widespread minor damage. There is minor stream bed movement evident. Debris is restricting the channel slightly. [6]							
Appraisal ratings - water adequac	Equal to present minimum cri	Equal to present minimum criteria [6]			Structurally deficient [1]				
Pier or abutment protection					28.9				
Culverts Not applicable. Used	if structure is not a culvert. [N]								
Traffic safety features - railings									
Traffic safety features - transition									
Traffic safety features - approach									
Traffic safety features - approach guardrail ends									
Inspection date March 2007 [0307] Designated inspection frequency 24 Months									
Underwater inspection	Not needed [N]	Underwater inspection date							
Fracture critical inspection	Every two years [Y24]	Fracture critical ins	spection date	March 2007 [03	07]				
Other special inspection	Not needed [N]	eded [N] Other special inspection date							