

# HistoricBridges.org - National Bridge Inventory Data Sheet

2012 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

## Basic Information

Minnesota [27]	Ramsey County [123]	Roseville [55852]	1.0 Mi East of Jct TH 51	45-00-37 = 45.010278	093-08-48 = - 93.146667
5723	Highway agency district 5	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 36	TH 36	Toll On free road [3]	Features intersected	LEXINGTON AVE(CSAH 51)	
Design - main	Concrete [1]	Design - approach	Kilometerpoint	0 km = 0.0 mi	
1	Frame [07]	0	Year built	1938	Year reconstructed #Num!
		Other [00]	Skew angle	0	Structure Flared
			Historical significance	Bridge is eligible for the NRHP. [2]	
Total length	19.5 m = 64.0 ft	Length of maximum span	19.5 m = 64.0 ft	Deck width, out-to-out	22.3 m = 73.2 ft
Inventory Route, Total Horizontal Clearance	19.5 m = 64.0 ft	Curb or sidewalk width - left	0.9 m = 3.0 ft	Curb or sidewalk width - right	0.9 m = 3.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection	Not applicable (applies only to structures with no deck) [N]				
Type of membrane/wearing surface					

## Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	39.2 metric ton = 43.1 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	65.3 metric ton = 71.8 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	M 18 / H 20 [4]

### Functional Details

Average Daily Traffic	85000	Average daily truck traffi	3	%	Year	2004	Future average daily traffic	85000	Year	2029
Road classification	Principal Arterial - Other Freeways or Exp		Lanes on structure	4		Approach roadway width	25 m = 82.0 ft			
Type of service on bridge	Highway-pedestrian [5]		Direction of traffic	2 - way traffic [2]		Bridge median	Closed median with non-mountable bar			
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Highway, with or without ped		Lanes under structure	3		Navigation control	Not applicable, no waterway. [N]			
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	30.48 m = 100.0 ft			
Minimum lateral underclearance reference feature	Highway beneath structure [H]									
Minimum lateral underclearance on right	1.8 m = 5.9 ft					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	4.45 m = 14.6 ft		Minimum vertical underclearance reference feature	Highway beneath structure [H]						
Appraisal ratings - underclearances	Meets minimum tolerable limits to be left in place as is [4]									

### Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	805000	Roadway improvement cost	66000
	Length of structure improvement	23 m = 75.5 ft	Total project cost	994000
	Year of improvement cost estimate	2011		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

## Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - superstructure	Poor [4]	Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]
Condition ratings - substructure	Fair [5]	Appraisal ratings - deck geometry	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - deck	Poor [4]		
Scour	Bridge not over waterway. [N]		
Channel and channel protection	Not applicable. [N]		
Appraisal ratings - water adequacy	N/A [N]	Status evaluation	Structurally deficient [1]
Pier or abutment protection		Sufficiency rating	61
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	May 2011 [0511]	Designated inspection frequency	12 Months
Underwater inspection	Unknown [N00]	Underwater inspection date	
Fracture critical inspection	Unknown [N00]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	