The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Info	ormation									46-29-42 =	087-06-26 = -
Michigan [26] Alger County [003]		Onota [6	Onota [60820] 0.4 MI E OF		F MARQUETTE COL		46.495000	87.107222			
0210204	1000B010	Highway agend	cy district 1	Owner	State Highway A	Agency [01]		Maintenance	e responsibility	State Highway Ag	ency [01]
Route 2	8	M-28			Toll On fre	e road [3]		Features interse	cted SAND RIVE	R	
Design - main	Concrete [1 Arch - Deck		Design - approach	Other [00]		Kilometer Year built Skew ang Historical	1939 le 0	Structure F	constructed N/A	[0000]	
,		Horizontal Clearance	ngth of maximum 11.5 m = 37. oncrete Cast-in	7 ft C	ı = 65.9 ft urb or sidewalk wi	Deck wi	-	out 12.3 m = 40	4 ft Bridge road		0.4 m = 1.3 ft
Deck prot		aring surface	ituminous [6]								
8 0 km - 5 5 mi			rmine inventory rating Load Factor(LF) [1] rmine operating rating Load Factor(LF) [1] Equal to or above legal loads [5]			, ,			30.5 metric ton 50.8 metric ton 18 / H 20 [4]		

Functional Details	
Average Daily Traffic 3093 Average daily tr	ruck traffi 10 % Year 2007 Future average daily traffic 4926 Year 2018
Road classification	[02] Lanes on structure 2 Approach roadway width 12.2 m = 40.0 ft
Type of service on bridge Highway [1]	Direction of traffic 2 - way traffic [2] Bridge median
Parallel structure designation No parallel structure	e exists. [N]
Type of service under bridge Waterway [5]	Lanes under structure 0 Navigation control
Navigation vertical clearanc 0 = N/A	Navigation horizontal clearance 0 = N/A
Minimum navigation vertical clearance, vertical lift bri	dge Minimum vertical clearance over bridge roadway 99.99 m = 328.1 ft
Minimum lateral underclearance reference feature F	eature not a highway or railroad [N]
Minimum lateral underclearance on right 99.9 = Unlin	mited Minimum lateral underclearance on left 0 = N/A
Minimum Vertical Underclearance 0 = N/A	Minimum vertical underclearance reference feature Feature not a highway or railroad [N]
Appraisal ratings - underclearances N/A [N]	
Repair and Replacement Plans	
Type of work to be performed	Work done by
	Bridge improvement cost Roadway improvement cost
	Length of structure improvement Total project cost
	Year of improvement cost estimate
	Border bridge - state Border bridge - percent responsibility of other state
	Border bridge - structure number

Inspection and Sufficiency									
Structure status Open, no res	striction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]						
Condition ratings - superstructur	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present minimum criteria [6]						
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings -	Somewhat better than minimum adequacy to tolerate being left in place as is [5]						
Condition ratings - deck	Satisfactory [6]	deck geometry							
Scour	Bridge foundation	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]							
Channel and channel protection		Bank is beginning to slump. River control devices and embankment protection have widespread minor damage. There is minor stream bed movement evident. Debris is restricting the channel slightly. [6]							
Appraisal ratings - water adequac	Better than prese	nt minimum criteria [7]	Status evaluation						
Pier or abutment protection			Sufficiency rating 78.6						
Culverts Not applicable. Used	if structure is not a culver	rt. [N]							
Traffic safety features - railings	I	npected feature meets currently acce	eptable standards. [1]						
Traffic safety features - transition	_	npected feature meets currently acce							
Traffic safety features - approach	n guardrail I	Inpected feature meets currently acceptable standards. [1]							
Traffic safety features - approach	n guardrail ends								
Inspection date May 2009 [09]	509] Desig	ted inspection frequency 24 Months							
Underwater inspection	Not needed [N]	Underwater inspec	ection date						
Fracture critical inspection	Not needed [N]	Fracture critical ins	nspection date						
Other special inspection	Not needed [N]	Other special insp	pection date						